

STYLE REF: TC130

STYLE NAME: MAINE

RockFall®
INDUSTRY DEFINING SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S1P SRC | UK 6-14 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, WITH PROTECTIVE TOECAP AND MIDSOLE, MAINE IS COMFORTABLE AND LIGHTWEIGHT, IT'S DEVELOPED WITH SPECIALIST COMFORT MATERIALS INCLUDING A SHOCK ABSORBING DUAL DENSITY PU NITRILE RUBBER OUTSOLE AND ACTIV-STEP® PU ANTI-FATIGUE COMFORT FOOTBED.

TC130



activ
step

Upper Material

Full grain black nubuck with breathable mesh panels

Protective Components

Protective fibreglass toecap and composite anti-penetration flexi-midsole

Lining Materials

Moisture wicking breathable mesh fabric lining

Scuff Cap and Outsole

Shock absorbing dual density PU nitrile rubber outsole

Footbed

Activ-Step® PU anti-fatigue comfort footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/06/2019

WWW.ROCKFALL.COM | WWW.ROCKFALL.COM/PRODUCTS/MAINE

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

EC DECLARATION OF CONFORMITY



Head Office & Distribution Centre

Rock Fall UK Limited
Unit 1 Major House
Wimsey Way
Alfreton, Derbyshire
England. DE55 4LS

E: sales@rockfall.co.uk
T: 01773 608616

www.rockfall.co.uk

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Declares that the PPE described hereafter;

TOMCAT MAINE TC130

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00331245** Issued by:-

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Signature:

Position: Director

Date: 01/01/2017



EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to

: Rock Fall UK Ltd
Wimsey Way, Alfreton Trading Estate, Derbyshire,
UK DE55 4LS

Manufacturer

Date of Issue

: 12 March 2013

Expiry Date

: 25 January 2018

Certificate No.

: LEC FI00331245 (Extension to certificate LEC FI00330577)

Product Reference(s)

: RF007, TC130

Description

Construction	:	Cemented
Toecap	:	PEP# Composite
Midsole	:	PEP# Composite
Last	:	#PEP-PL
Sole	:	PS-2050# MD + RB
Test Report(s)	:	See Technical File
Size Range	:	UK 6 – 13
Category	:	S1P SRC

Assessor

P. Williamson

Certification Manager

For and on behalf of ITS Testing Services (UK) Limited

12/03/2013

Date

12/03/2013

Date

Registered in England No. 1408264 Registered Office: 25 Savile Road, London W1S 2ES

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



Number: GZHT90235625

Tests Conducted (As Requested By The Applicant)

2 Outsole Slip Resistance (EN ISO 20344:2004/A1:2007 (5.18), SRA, 23°C):

<u>Size</u>	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>		<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 40</u>	Heel Part	0.48	Min. 0.28	Pass
	Flat Contact	0.53	Min. 0.32	Pass
<u>Size 42</u>	Heel Part	0.43	Min. 0.28	Pass
	Flat Contact	0.50	Min. 0.32	Pass
<u>Size 47</u>	Heel Part	0.50	Min. 0.28	Pass
	Flat Contact	0.51	Min. 0.32	Pass

3 Impact Resistance (Toe Protection) (EN ISO 20344:2004/A1:2007 (5.4)):

<u>Size</u>			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 40</u>	Left:	16.0 mm	Min. 13.5 mm	Pass
			(#)	
	Right:	14.5 mm	Min. 13.5 mm	Pass
			(#)	
<u>Size 42</u>	Left:	16.0 mm	Min. 14.0 mm	Pass
			(#)	
	Right:	15.5 mm	Min. 14.0 mm	Pass
			(#)	
<u>Size 47</u>	Left:	17.0 mm	Min. 15.0 mm	Pass
			(#)	
	Right:	16.5 mm	Min. 15.0 mm	Pass
			(#)	

Remark: # = In Addition, The Toecap Shall Not Develop Any Cracks On The Test Axis Which Go Through The Material, ie. Through Which Light Can Be Seen.

Expended Uncertainty: 0.49 (Urel), with k= 1.96 at 95% confidence level



Number: GZHT90238494

Tests Conducted (As Requested By The Applicant)

Outsole Slip Resistance (EN ISO 20344:2004/A1:2007 (5.18), SRB, 23°C):

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 40</u>	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.14	Min. 0.13	Pass
	Flat Contact	0.18	Min. 0.18	Pass
<u>Size 42</u>	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.14	Min. 0.13	Pass
	Flat Contact	0.19	Min. 0.18	Pass
<u>Size 47</u>	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.13	Min. 0.13	Pass
	Flat Contact	0.18	Min. 0.18	Pass